

SC-2007-PEG IP Phone with PoE;

SC-2007-IPG IP Phone with AC Power;

2 SIP, TR-069, 10/100/1000M Ethernet ports,



SC-2007-PEG/ SC-2007-IPG IP Phone with TR-069 is a compact office IP Phone with rich features. It has 128*64 HD graphic LCD up to 4 -line display; HD Sound Quality, 5programmable keys, and friendly user interface to satisfy users communication needs.

Key Features:

- ♦ Support 2 lines;
- Support 38.5° demountable bracket;
- Support 5 programmable keys(2 Line keys, Up & Down keys, Redial key);
- ♦ Auto-provision, HTTP/HTTPS/TFTP/FTP;

Phone Features:

- ♦ 2 SIP accounts, MWI(Line1)
- Call hold, Call waiting, Call forward, Call return; Call transfer (blind/busy/ask)
- ♦ Caller ID display, Redial, Mute, DND
- ♦ Auto-answer, 3-way conferencing
- ♦ Speed dial, SMS, Voicemail
- ♦ Tone scheme, Volume control
- ♦ Direct IP call without SIP proxy
- ♦ Ring tone selection/import/delete
- ♦ Black list, Hand-free indicator.
- ♦ Call history: dialed/received/missed;
- ♦ Soft keys programmable, Supports PC control
- ♦ Multi-Language:

Chinese, English, French, Russian, Italian, Polish, Portuguesa, Portuguesa-Brasil, Spanish, Turkish

Advanced Features:

- ♦ 5 programmable keys
- ♦ XML Phone Book search and input & output
- Enterprise phone book(800 entries)
- Personal Phonebook(300 entries)
- ♦ LDAP phone book

Optional Feature:

♦ TR069, IPv6, HTTPS web management, 802.1x, OPEN VPN

IP PBX System Integration:

- ♦ Busy lamp field (BLF), BLF list
- ♦ Bridged line appearance (BLA)
- DND & Forward synchronization
- Intercom, Paging, Music on hold

- ♦ Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection
- ♦ Network conference, Distinctive ring tone

Codes and Voice Features:

- ♦ Wideband Codec: G.722
- ♦ Narrowband codec: G.711µ/A, G.726, G.729AB,iLBC
- ♦ VAD, CNG, AEC, AGC, Full-duplex,

Management:

- ♦ Auto-provision via FTP/TFTP/HTTP/HTTPS
- ♦ Configuration: browser/phone/auto-provision
- ♦ Trace package and system log export

Network Features:

- ♦ SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode;
- ♦ SRTP voice encryption(RFC3711)
- ♦ Redundant server support
- ♦ NAT Traversal: STUN mode
- ♦ DTMF: In-Band, RFC2833, SIP Info, Auto
- ♦ HTTP Web Management
- ♦ IP Assignment: Static/DHCP/PPPoE
- ♦ Bridge/Router mode for PC port
- ♦ TFTP/DHCP/PPPoE client
- ♦ Telnet/HTTP/HTTPS server, DNS client, NAT/DHCP server

Security:

- ♦ VLAN QoS (802.1pq), SRTP
- ♦ Transport Layer Security (TLS)
- ♦ Digest authentication using MD5/MD5-sess
- ♦ Secure configuration file via AES encryption
- ♦ Encryption for configuration file
- ♦ Phone lock for personal privacy protection
- ♦ Admin/User 2-level configuration mode , LLDP, CDP
- ♦ L2TP VPN tunneling protocol added

Physical Features:

- ♦ 128*64 graphic LCD with back light
- ♦ 25 keys, including 5 programmable keys,
- ♦ 2 LEDs: 2* account lights, including MWI(L1)
- ♦ 1* RJ9 handset port
- ♦ 1* RJ9 headset port
- ♦ 2xRJ45 10/100/1000M Ethernet ports
- ♦ Power adapter: AC 100~240V input and
- ♦ DC 5V/1A output
- ♦ POE ,IEEE 802.3af,class 0(Option)
- ♦ Power consumption: 1.5W
- ♦ Net weight: 0.62kg
- ♦ Dimension: 180x157x33mm
- ♦ Operating humidity: 10~95%
- ♦ Storage temperature: up to 60°C

SunComm Technology Co., Ltd

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

www.SunComm-4glte.com www.SunComm.com.tw

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393

E-mail: sales2@SunComm.com.tw

China: www.SunComm.cn

Tel: +86-136 8884 2805

