



# SunComm

SunComm Technology Co., Ltd

## SC-3082-IP/SC-3082-PE IP Phone with HD Voice, PoE, Color LCD, 3SIP LINE,



SC-3082-IP/SC-3082-PE is a highly innovative based SIP IP phone, It can perfectly satisfy with all kinds of the businessman communication. It integrates with 2.4" 320x240-pixel color LCD with backlight, a large resolution display screen, elegant and intuitive user interface. SC-3082-IP/SC-3082-PE offers HD handset, HD speaker and HD codec (G.722), with a rich set of business communication features that can definitely improve working efficiency and sense. It is highly suitable for SMEs, Home Office and ISP applications. SC-3082-IP/SC-3082-PE help user connect the network simply and enjoy the network easily.

### Key Features

- **Color LCD** with backlight.2.4" 320x240-pixel
- HD Voice: HD Codec, HD Speaker, HD Handset.
- 3 SIP accounts and support 3-way conference, SMS.
- 2 x 10/100Mbps PC & LAN, PoE, 1xRJ9 Headset port.
- One standard (42.5°) level bracket and wall-mountable.
- XML/LDA, Contact Search.
- Auto-provision, HTTP/TFTP/FTP.

- Multi-language: Chinese, English, French, Russian, Italian, Polish, Portuguesa, Spanish, Turkish etc...

### Phone Features

- ◆ 3 SIP accounts, MWI(Line1)
- ◆ Call hold, Call waiting, Call forward, Call return, Call transfer (blind/busy/ask)
- ◆ Caller ID display, Redial, Mute, DND
- ◆ Auto-answer, 3-way conferencing
- ◆ Speed dial, SMS, Voicemail
- ◆ Tone scheme, Volume control
- ◆ Direct IP call without SIP proxy
- ◆ Ring tone selection/import/delete
- ◆ Black list, Hand-free indicator.
- ◆ Call history: dialed/received/missed (50 -entries)
- ◆ Soft keys programmable, Supports PC control
- ◆ Support switching SIP server & Second server
- ◆ **Optional Feature:** TR069 , IPv6 , HTTPS web management , 802.1x , OPEN VPN

### Advanced Features

- ◆ XML Phone Book search and input & output
- ◆ Enterprise phone book (800 entries)
- ◆ Personal Phonebook (300 entries)
- ◆ LDAP phone book
- ◆ 15 paperiess programmable keys

### IP PBX System Integration

- ◆ Busy lamp field (BLF), BLF list
- ◆ Bridged line appearance (BLA)
- ◆ DND & Forward synchronization
- ◆ Intercom, Paging, Music on hold
- ◆ Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection
- ◆ Network conference, Distinctive ring tone

### Codes and Voice Features

- ◆ Wideband Codec: G.722
- ◆ Narrowband codec: G.711μ/A, G.726, G.729AB, iLBC, VAD, CNG, AGC, AEC, Full-duplex

### Security

- ◆ VLAN QoS (802.1pq), SRTP
- ◆ Transport Layer Security (TLS)
- ◆ Digest authentication using MD5/MD5-sess
- ◆ Secure configuration file via AES encryption
- ◆ Encryption for configuration file
- ◆ Phone lock for personal privacy protection

- ◆ Admin/User 2-level configuration mode, LLDP, CDP
- ◆ L2TP VPN tunneling protocol-added

## Network Features

- ◆ SIP v1 (RFC2543), v2 (RFC3261)
- ◆ SIP connection: Proxy mode & Peering Points mode;
- ◆ SRTP voice encryption (RFC3711)
- ◆ Redundant server support
- ◆ NAT Traversal: STUN mode
- ◆ DTMF: In-Band, RFC2833, SIP Info, Auto
- ◆ HTTP Web Management
- ◆ IP Assignment: Static/DHCP/PPPoE
- ◆ Bridge/Router mode for PC port
- ◆ TFTP/DHCP/PPPoE client
- ◆ Telnet/HTTP/HTTPS server, DNS client, NAT/DHCP server

## Management

- ◆ Auto-provision via FTP/TFTP/HTTP/HTTPS
- ◆ Configuration: browser/phone/auto-provision
- ◆ Trace package and system log export

## Physical Features

- ◆ 2.4"320x240 color LCD; 34 keys including 2 programmable keys;
- ◆ 1xRJ9 headset port; 2xRJ45 10/100M Ethernet ports;
- ◆ Line keys with LED indicator: 3
- ◆ LED for call and message waiting indication;
- ◆ Dual-color (red or green) illuminated LEDs for line status information;
- ◆ 42.5° bracket and wall-mountable
- ◆ Power adapter: AC 100~240V input and
- ◆ DC 5V/1A output;
- ◆ Power over Ethernet, IEEE 802.3af, class 0
- ◆ Power consumption: 1.4-2.6W
- ◆ Net weight:
- ◆ Dimension:
- ◆ Operating humidity: 10~95%
- ◆ Storage temperature: up to 60°C

## Package Features

- ◆ Qty/CTN: 10 PCS
- ◆ N.W/CTN: 7.58kg
- ◆ G.W/CTN: 8.8kg
- ◆ Measurement: 0.068 CBM (±0.5%)

◆ Carton Measurement: 455x390x222mm

*SunComm* Technology Co., Ltd.

7F, No.53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

Tel.: +886 2 3234 1496; Fax: +886 2 3234 1393; Email: [sales2@SunComm.com.tw](mailto:sales2@SunComm.com.tw)

Website: [www.SunComm.com.tw](http://www.SunComm.com.tw) [www.SunComm.cn](http://www.SunComm.cn) [www.SunComm-4glt.com](http://www.SunComm-4glt.com)

