



SunComm

SunComm Technology Co., Ltd

**SC-3086-PE Desktop / Wall-mount Installation RJ45
Ethernet 6 Lines VOIP Phone
with HD Voice, PoE, Color LCD**



Key Features

2.8" 240x320-pixel color display with backlight

6 multi-functional line keys, up to 30 Paperless DSS Keys

Optima HD voice, Full-duplex speakerphone

Dual-port Gigabit Ethernet, integrated POE

1xBuilt-in USB Port;

Up to 6 SIP accounts, 3-way conferencing;

Wall-mountable, integrated stand with 2 adjustable angles

Phone Features

- ◆ **6 SIP accounts, Hotline**
- ◆ Call hold, Call waiting, Call forward, Call return
- ◆ Call transfer (blind/busy/ask)
- ◆ Caller ID display, Redial, Mute, DND
- ◆ Auto-answer, 3-way conferencing
- ◆ Speed dial, SMS, Voicemail Message Waiting Indication LED
- ◆ Tone scheme, Volume control
- ◆ Direct IP call without SIP proxy
- ◆ Ring tone selection/import/delete
- ◆ Black list, Hand-free indicator.
- ◆ Call history: dialed/received/missed;
- ◆ Multi-Language
- ◆ Soft keys programmable, Supports PC control

Advanced Features

- ◆ **Support up to 30 paperless DSS keys**
- ◆ XML Phone Book search and input & output
- ◆ Enterprise phone book 2000
- ◆ Personal phone book 1000
- ◆ LDAP phone book
- ◆ Functions customizable keys
- ◆ Support EHS

IP PBX System Integration

- ◆ **Busy lamp field (BLF), BLF list**
- ◆ Bridged line appearance (BLA)
- ◆ DND & Forward synchronization
- ◆ Intercom, Paging, Music on hold
- ◆ Call pickup, Dial Plan, Call recording Anonymous call, Anonymous call rejection

Codes and Voice Features

- ◆ Full-duplex
- ◆ Wideband Codec: G.722
- ◆ Narrowband codec: G.711 μ /A,
- ◆ G.726, G.729AB,iLBC
- ◆ VAD, CNG, AEC, AGC

Security

- ◆ LLDP, VLAN QoS (802.1pq),VPN(L2TP)
- ◆ Transport Layer Security (TLS)
- ◆ Digest authentication using MD5/MD5-sess
- ◆ Secure configuration file via AES encryption
- ◆ Phone lock for personal privacy protection
- ◆ Admin/User 2-level configuration mode

Network Features

- ◆ SIP v1 (RFC2543), v2 (RFC3261)
- ◆ DNS SRV (RFC3263)
- ◆ NAT Traversal: STUN mode
- ◆ DTMF: In-Band, RFC2833, SIP Info, Auto
- ◆ HTTP Web Management
- ◆ HTTPS Web Management is optional
- ◆ IP Assignment: Static/DHCP/PPPoE/Bridge/Router mode for PC port
- ◆ TFTP/DHCP/PPPoE client
- ◆ DNS client, NAT/DHCP server

Management

- ◆ Auto-provision via FTP/TFTP/HTTP/HTTPS
- ◆ SNMP V1/2 , TR069 is optional

Physical Features

- ◆ 240x320-pixel color display with backlight
- ◆ 37 keys, 8 LED lights,
- ◆ **Wall-mountable(Optional)**
- ◆ 1xRJ-9 **handset** port
- ◆ 1xRJ-9 **headset** port
- ◆ **2xRJ45 10/100/1000M Ethernet ports**
- ◆ Power adapter: AC 100~240V input and DC 12V/1A output
- ◆ **1x USB port**
- ◆ Power over Ethernet, IEEE 802.3af,class 0
- ◆ Power consumption: 2.5-3.5W
- ◆ Dimension: 185mm*188mm*62mm
- ◆ Operating humidity: 10~95%
- ◆ Storage temperature: up to 60°C

Package Features

- ◆ Qty/CTN: 10 PCS

SunComm Technology Co., Ltd

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

www.SunComm-4glte.com www.SunComm.com.tw

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393

E-mail: sales2@SunComm.com.tw

China: www.SunComm.cn

Tel: +86-136 8884 2805

