




## **SC-5030A-5GR Indoor Router WIFI 5G** **with 1WAN+4LAN+2RJ11**



The **SC-5030A-5GR** is a WiFi 6 AX3000 Gigabit 1GE WAN+3GE LAN dual-band Indoor wireless Router, upgraded to the latest 802.11ax standard and integrated with VoIP and wireless AP capabilities. It serves as a security solution for homes, remote broadband offices, and small-scale SOHO networks.

### **Application:**



## Specifications:

<b>Interface</b>	<ul style="list-style-type: none"> <li>● <b>1GE WAN+3GE LAN + WiFi6</b></li> </ul>
<b>Button</b>	<ul style="list-style-type: none"> <li>● Reset/WPS</li> </ul>
<b>User Interface</b>	<ul style="list-style-type: none"> <li>● 4*10/100/1000Mbps auto adaptive Ethernet interface, RJ45 connectors (1*WAN, 3*LAN)</li> </ul>
<b>WLAN Interface</b>	<ul style="list-style-type: none"> <li>● Compliant with IEEE802.11b/g/n/ac/ax</li> <li>● 2402 Mbps on 5GHz and 574Mbps on 2.4 GHz</li> <li>● 2.4GHz: 2*2(3dBi), 5GHz: 2*2(5dBi); External antennas</li> <li>● Maximum number of connected devices:128</li> </ul>
<b>WiFi Rate</b>	<ul style="list-style-type: none"> <li>● Wi-Fi 6: 802.11a/n/ac/ax 5GHz &amp; 802.11b/g/n/ax 2.4GHz</li> <li>● WiFi Encryption: WEP-64/WEP-128/ WPA/WPA2/WPA3</li> <li>● Support MU-MIMO &amp; OFDMA</li> <li>● Support Dynamic QoS</li> <li>● Support 1024-QAM</li> <li>● Support WMM</li> <li>● BSS-Coloring &amp; Beamforming &amp; Beam steering</li> <li>● Support WIFI Easy-mesh function</li> <li>● Seamless roaming</li> </ul>
<b>L3/L4</b>	<ul style="list-style-type: none"> <li>● Support IPv4, IPv6 and IPv4/IPv6 dual stack</li> <li>● Support DHCP/PPPOE/Statics</li> <li>● Support Static route, NAT</li> <li>● Support DMZ, ALG, UPnP</li> <li>● Support Virtual Server</li> <li>● Support NTP (Network Time Protocol)</li> <li>● Support DNS Client and DNS Proxy</li> </ul>
<b>DHCP</b>	<ul style="list-style-type: none"> <li>● Support DHCP Server &amp; DHCP Relay</li> </ul>
<b>Management</b>	<ul style="list-style-type: none"> <li>● WEB/Telnet/TR-069/SSH/CLI</li> <li>● Management/TR369/MQTT</li> </ul>
<b>Multicast</b>	<ul style="list-style-type: none"> <li>● Support IGMP Snooping (IGMPv1/v2/v3)</li> <li>● Support IGMP Proxy</li> <li>● Support MLD Snooping (MLDv1, MLDv2)</li> <li>● Support MLD Proxy</li> <li>● Support Fast leave</li> <li>● IPTV service</li> </ul>
<b>Security</b>	<ul style="list-style-type: none"> <li>● Support local access control</li> <li>● Support IP address filtering</li> <li>● Support URL filtering</li> <li>● Support Anti-DDoS attack function</li> <li>● Support Anti-port scanning function</li> <li>● Suppression of protocol-specific broadcast/multicast packets (e.g. DHCP, ARP, IGMP, etc.)</li> <li>● Support Anti-Intranet ARP Attack</li> <li>● Support Parental control function</li> </ul>

<b>Power Supply</b>	<ul style="list-style-type: none"> <li>● DC12V, 1A, ≤12W</li> </ul>
<b>Dimensions</b> <b>Net weight</b>	<ul style="list-style-type: none"> <li>● 179.9 X 104.1 X 30.8 (mm)</li> <li>● 185g</li> </ul>
<b>Operating Temperature:</b>	<ul style="list-style-type: none"> <li>● Working temperature: -30°C - 60°C</li> <li>● Working humidity: 5 - 95% (non-condensing)</li> <li>● Storing temp: -40~+85°C</li> <li>● Storing humidity: 5~ 95% (non-condensing)</li> </ul>

## *SunComm* Technology Co., Ltd

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

[www.SunComm.com.tw](http://www.SunComm.com.tw) [www.SunComm-4glt.com](http://www.SunComm-4glt.com) [www.SunComm.asia](http://www.SunComm.asia)

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393

E-mail: [gary@SunComm.com.tw](mailto:gary@SunComm.com.tw)

China: [www.SunComm.cn](http://www.SunComm.cn) Tel: +86-136 5142 2805

