



SunComm

SunComm Technology Co., Ltd

SC-9034-4GP 4G Fixed Wireless Phone

with 2.4G WIFI, SIP, 1 x RJ45 port

4G band 23dBm; WIFI 16.5 dBm



SC-9034-4GP 4G LTE Fixed Wireless Phone supports HD voice call, the device uses 2.4 inch 240x320 resolution, support 2.4G WIFI connection, And can be used as a WIFI hotspot. It is very suitable for wireless office. It has excellent hardware echo suppression and noise reduction effect, Support standard SIP 2.0 protocol, compatible with most soft PBX, IMS and IPPBX system, and various SIP protocol audio and video terminals.

SC-9034-4GP Wireless fixed is a multifunctional communication terminal, It can be used in the company extension and network IP phone operation network and users with Internet access. Can be connected the business 4G network, with the support of the operator, the communication cost is extremely low. Can also be used as a cost-effective and stable in various proprietary networks communication tool that is extremely high and most in line with traditional usage habits.

Main features:

- 2.4 inch color screen
- WIFI hotspot
- Built-in WIFI (IEEE802.11 b/g/n) 2.4G
- Support HD audio calls
- Support SIP 2.0 (RFC3261)
- Support SIP UDP / TCP / TLS
- Three-party audio conference

Specifications:

LCD	2.4 -inch color screen	
SIM Card	Standard SIM card	
Key	3*4+25 keys	
PBX compatibility	Broadsoft Asterisk Trixbox Freeswitch Huawei PBX compatibility Avaya ZTE Yeastar	
USB	Micro usb charging port	
Band	Type	SC-9034-4GP
	FDD_LTE	B1(2100MHz)/B3(1800MHz)/ B5(850MHz)/B7(2600MHz)/B8(900MHz)/B20(800MHz)
	TDD_LTE	B38(2600MHz)/B40(2300MHz)/ B41(2500MHz)
	3G band	B1(2100MHz)/B8 (900MHz)
	2G band	B2(1900MHz)/B3(1800MHz)/B5(850MHz)/B8(900MHz)
Speed-dial	M1-M3 2-9 number keys	
Phone book	Support 500 contacts	
Call log	Support 50 records	

voice message	Unread voice message reminder
Audio Features	G.722/G.729/AMR/AMRWB/GSM/PCMA/PCMU/SPEEX/ILB/DTMF /ISACWB/OPUS. Supports high quality Audio call. VAD/CNG/AGC/ANS/AEC.
DTMF Features	RFC 2833 、 SIP INFO
SIP Features	Supports SIP 2.0 (RFC3261) Supports 2 SIP Account Supports SIP UDP/TCP/TLS
Network protocol	HTTP/TR069/RTP/SRTP
Phone Features	Add/delete contacts/missed call reminder/Caller ID with name/Ring tone select. Redial/Mute/Call hold/Do Not Disturb/Auto Answer. Call transfer/busy transfer/unconditional transfer. Voice mail
Power supply	DC5V input, built in 1000ma/H battery
Physical Parameters	Power supply: input 100-240V, output 1A/5V Environment: temperature -10℃~ 50℃ humidity 10%~ 90% Packaging accessories: one host, one handle, one power adapter.

SunComm Technology Co., Ltd

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

www.SunComm-4glt.com www.SunComm.com.tw www.SunComm.asia

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393 E-mail: sales3@SunComm.com.tw

China: www.SunComm.cn Tel: +86-136 5142 2805

