



*SunComm*

SunComm Technology Co., Ltd

## **SC-9068-WPD 2.4GHz/5.0GHz (Dual WiFi)**

**WiFi IP Phone Portable with HD voice,**

**Bluetooth Headset, Color LCD**



### **Main features of SC-9068-WPD Dual Wifi IP Phone Portable:**

- **2 SIP Line**
- **Android OS, 2.4" 320 x 240 TFT LCD**
- **Video (optional)**
- Call hold, mute, DND (Don't Disturb)
- One-touch speed dial
- Call forward, call waiting, call transfer
- SMS, Emergency call
- Redial, call return, auto answer
- 3-way conferencing

- Ring tone selection/ import/ delete
- Set date time manually or automatically
- Dial plan
- Bluetooth headset jack
- Color LCD

#### Audio features:

- HD voice: HD handset, HD speaker
- Codec: G.722, G.711 (A/μ), G.723, G.729AB, GSM, iLBC, Speex-WB, OPUS
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC

#### Management:

- Configuration: browser/phone/auto-provisioning
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Phone lock for personal privacy protection
- Reset to factory, reboot
- System log

#### Network and security:

- Wi-Fi client
- WLAN Supports static IP, dynamic IP
- NAT&NAPT with VPN pass-through Virtual Server
- Automatic receipt of IP address with DHCP Server - delete
- Security through WEP, WPA-PSK, WPA2-PSK, WDS
- Simple handling and management over web interface
- SIP v1 (RFC2543), v2 (RFC3261)
- NAT transverse: STUN、ICE, TURN mode
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- QoS: ToS/DSCP; Layer 3
- media protocol: RTP/SRTP
- signaling transport protocol: TCP/UDP/TLS
- Digest authentication using MD5/MD5-sess
- VPN type: OpenVPN, IEEE802.1X

#### WIFI:

- IEEE 802.11b/g/n, IEEE 802.3、IEEE 802.3u
- **2.4GHz/5.0GHz (Dual WIFI)**
- Data rate Speed up to 300Mbps
- Channel bandwidth: 20MHz/40MHz

### History:

- Missed calls
- Dialed calls
- Received calls
- Rejected calls
- Call time

### Setting:

- Language
- Backlight
- Brightness
- Ringtone
- Date & time
- Shortcut
- Restore factory settings
- Idle display settings
- Phone lock
- Screen lock
- Blacklist
- Call settings (Call forward, Call waiting & DND)
- Network connection

### Power:

- SoC platform, **7 + days standby, 5+ hours talking**
- Operating voltage: 100 to 240V AC 50/60Hz
- **Battery: 3400MAH**

### Physical & Environmental:

- Desktop Power Input: 100V-240V AC
- Output: 5V DC 1A
- Dimensions: 155X55X22mm
- Weight: 170G (handset & charger)
- Ambience temperature: 0°C ~ 40°C
- Ambience temperature: 0°C ~ 40°C
- Air pressure: 86 ~ 106kPa

*SunComm* Technology Co., Ltd

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

[www.SunComm-4glt.com](http://www.SunComm-4glt.com) [www.SunComm.com.tw](http://www.SunComm.com.tw)

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393 E-mail: [sales2@SunComm.com.tw](mailto:sales2@SunComm.com.tw)

China: [www.SunComm.cn](http://www.SunComm.cn) Tel: +86-136 8884 2805

