



SunComm

SunComm Technology Co., Ltd

SC-9072-PE IP Phone;
SC-9072-PEG IP Phone with Gigabit,
2SIP, HD Voice, POE optional



As fashionable entry-level IP phone, the SC-9072-PE and SC-9072-PEG VoIP phone support 2 VoIP accounts, 6 programmable keys, working with adjustable multi-angle stand, built-in Power over Ethernet (PoE) and superb high definition (HD) sound quality, easy-to-use and powerful features, together with reasonable price delivering excellent voice communications solution.

FEATURES:

- ◆ 2 lines indicators with individual SIP account profiles
- ◆ Call waiting, hold, mute, transfer (blind or attended), forward, 3-way conference, dial plan, hotline, DND, etc.
- ◆ Breathing LED ring to indicating message and state
- ◆ Full duplex speaker phone w/advanced audio echo cancellation
- ◆ Headset RJ9 port
- ◆ Large phonebook (up to 500 contacts) and call history (up to 100 records)
- ◆ Volume Adjustable, Ring tones Selectable
- ◆ Country Ringtone Signal
- ◆ XML Browser
- ◆ Keypad lock
- ◆ Action URL/URI
- ◆ LDAP Phone Book
- ◆ 6 programming keys set as speed dial, SOS, call processing and BLF etc., with green LED indicator
- ◆ Two angle desktop & wall mount
- ◆ Compatible with all leading IP PBX Systems

Highlights:

- ◆ 2 SIP accounts
- ◆ PoE
- ◆ HD voice
- ◆ Opus codec support
- ◆ RJ9 Headset
- ◆ High dot matrix 128x64 LCD display
- ◆ Auto provision
- ◆ Wall mountable
- ◆ VMS SaaS DIY configure & FoTA
- ◆ Two-port 10/100M Ethernet Switch
- ◆ Two-port 10/100/1000M Ethernet Switch
- ◆ Stand with 2 adjustable angles
- ◆ RFID (optional)
- ◆ TR069

Display and Indicator	<ul style="list-style-type: none"> ◆ 128 x 64-pixel graphical LCD with backlight or 2.8' 320 x 240 TFT LCD ◆ LED for call and message waiting indication ◆ Dual-color (red or green) illuminated LEDs for line status information ◆ Intuitive user interface with icons and soft keys ◆ Caller ID with name number Power saving
Interface	<ul style="list-style-type: none"> ◆ 2 x RJ45 10/100M Ethernet port ◆ 2 x RJ45 10/100/1000M Ethernet port ◆ Power over Ethernet (IEEE 802.3af), class 2 ◆ 1 x RJ9 (4P4C) handset port ◆ 1 x RJ9 (4P4C) headset port
Networking Features	<ul style="list-style-type: none"> ◆ SIP v1 (RFC2543), v2 (RFC3261) ◆ DNS SRV (RFC3263) ◆ Redundant server support ◆ NAT Traversal: STUN mode ◆ DTMF: In-Band, RFC2833, SIP Info ◆ Proxy mode and peer-to-peer SIP link mode ◆ IP Assignment: Static/DHCP/PPPoE ◆ TFTP/DHCP/PPPoEclient ◆ HTTP/HTTPS server ◆ DNS client, ◆ NAT/DHCP ◆ 802.1Q VLAN ◆ VPN (Open VPN/L2TP) ◆ Time and date synchronization using SNTP
Directory	<ul style="list-style-type: none"> ◆ Local phonebook up to 1000 entries ◆ Black list ◆ XML/LDAP remote phonebook ◆ Smart dialing ◆ Phonebook search/import/export ◆ Call history: dialed/received/missed/forwarded
Management	<ul style="list-style-type: none"> ◆ Syslog ◆ Auto-provision via FTP FTP/TFTP/HTTP/HTTPS ◆ Configuration: browser/auto-provision ◆ Factory configuration customized ◆ TR069 ◆ VMS
IP PBX Features	<ul style="list-style-type: none"> ◆ MWI ◆ Music on hold, Intercom

	<ul style="list-style-type: none"> ◆ Call Pickup, Group call, Call recording ◆ Anonymous Call, Anonymous Call Rejection ◆ Busy Lamp Field (BLF) ◆ Hot-desking, Flexible seating
Audio Features	<ul style="list-style-type: none"> ◆ HD Voice with high volume ◆ Hearing Aid Compatible (HAC) ◆ Codec: Opus G.722, G.729, G.711,G723, G726, ◆ VAD, CNG, AEC, PLC, AJB, AGC ◆ Full-duplex speakerphone with AEC
Security	<ul style="list-style-type: none"> ◆ Supports HTTPS (SSL) ◆ Supports SRTP for Voice Data Encryption ◆ Supports Login for Administration ◆ SIP Over TLS
Physical & Environmental	<ul style="list-style-type: none"> ◆ Color: Black ◆ Wall mountable ◆ External AC adapter: AC 100~240V input and DC 5V/600Ma output ◆ Dimensions: 210 x 170 x 45 mm ◆ Weight: 680g (base unit & handset) ◆ Power consumption (PSU): 2-3 W ◆ Power consumption (PoE): 3-4 W ◆ Operating humidity: 10~95% ◆ Operating temperature: -10 ~50°C(+14~122°F)
Package Features	<ul style="list-style-type: none"> ◆ Package content: IP phone, Handset with handset cord, Ethernet Cable (1.5m CAT5E UTP Cable)-Stand, Quick Start Guide, Power Adapter(Optional) ◆ Qty/CTN: 10PCS ◆ G.W/CTN: 10kg ◆ Giftbox size: 260 x 225 x 72 mm ◆ Carton Meas.: Size: 350 x 295 x 350 mm

SunComm Technology Co., Ltd

7F, No. 53, Jian-Kang Rd., Zhong-he Dist., New Taipei City, Taiwan 23586

www.SunComm-4glte.com www.SunComm.com.tw

Tel: 886-2-3234 1496 Fax: 886-2-3234 1393 E-mail: sales2@SunComm.com.tw

China: www.SunComm.cn Tel: +86-136 8884 2805

